TECHNICAL DATA SHEET



SS12062L

Fire Exit - Keep Clear (450 x 150mm)



Provided To Direct You To Safety • Available In 6 Materials

PRODUCT DESCRIPTION

Emergency escape signs are provided to guide you from wherever you are in a building, via a place of relative safety (the escape route) to the place of ultimate safety (the assembly area).

FEATURES & BENEFITS

- Rigid Plastic: Lightweight, gloss white PVC with high impact strength.
 Suitable for both internal and external safety signs. Easily drilled for wall fixing.
- Self-Adhesive Vinyl: A high gloss, flexible PVC vinyl with self-adhesive backing. Suitable for applying to most smooth, dry and clean surfaces. Ideally suited for internal signs.
- Photoluminescent Rigid Plastic: 1.2mm rigid PVC with photoluminescent pigmentation. Afterglow properties PSPA Class C grade, as measured to DIN 6751, provides razor sharp definition in black out conditions.
- Photoluminescent Self Adhesive: Flexible PVC with photoluminescent pigmentation. Afterglow properties exceed PSPA Class C grade, as measure to DIN 6751, provides razor sharp definition in blackout conditions.
- Rigid Plastic with Self Adhesive Back: Rigid PVC provides a durable finish, whilst a high tack self-adhesive backing removes the need for drilling, screwing or additional adhesive fixings.
- Floor Graphic: Sub surface printed and over laminated in hard wearing anti-slip polycarbonate film.

Dimensions: 450 x 150mm

For further information and the latest technical specification, please request a copy of the Manufacturers official data sheet. E&O.E.



V1.0